

AGRI SHIFT ULV**PRODUCT DESCRIPTION**

Agri Shift ULV Fully Synthetic Universal Tractor Transmission Oil (UTTO) is formulated with synthetic base stocks and advanced additives. Agri Shift ULV technology provides mission critical reliability in machines that require high shear stable oils and extended drain intervals. Agri Shift ULV has been formulated to meet Volvo WB 102 requirements of a UTTO providing excellent shear stability and high temperature gear protection. The product is designed to provide greater power transfer to gears thus reducing fuel consumption and providing optimal cold weather operation.

APPLICATIONS & BENEFITS

- Meets Volvo WB 102 specification.
- Mission critical reliability in transmissions and hydraulic systems.
- Fully Synthetic formulation provides excellent thermal protection and shear stability in both cold and hot operating conditions.
- Increased power transfer provides optimal cold weather operation and reduced fuel consumption.

PACK SIZES AVAILABLE

20L - 200L

SPECIFICATIONS

Volvo WB 102

TYPICAL CHARACTERISTICS

Agri Shift ULV	UNITS	VALUES
VISCOSITY	cSt @ 40°C	38.6
	cSt @ 100°C	7.45
SPECIFIC GRAVITY	@ 15°C	0.851
VISCOSITY INDEX		163
POUR POINT	°C	-39
FLASH POINT	°C	208

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.