



AGRI MONO T2 30W

PRODUCT DESCRIPTION

Agri Mono T2 30W is a Monograde Universal Tractor Transmission Oil (UTTO) specially designed for agricultural hydraulic and hydrostatic systems as well as a wide range of tractor transmissions. Agri Mono T2 is formulated to meet a wide range of specifications reducing the need to carry multiple Tractor Transmission fluids. The product is suitable for use in equipment fitted with wet brakes and can service almost all agricultural hydraulic and hydrostatic transmission systems. High Performance additives provide excellent friction control in brakes, reducing chatter and prolonged service life.

APPLICATIONS & BENEFITS

- Suitable for use in a wide range of transmissions, hydraulic systems, and drive trains in agricultural equipment.
- Advanced formulation reduces noise and chatter in wet brake systems.
- Robust Monograde formulation offers less oil shear and extended service life of the oil.
- Wide range of industry specifications reduces the need to carry multiple oils.

PACK SIZES AVAILABLE

5L - 20L

SPECIFICATIONS

- API GL-4
- Allison C-4
- Caterpillar TO-2
- CNH MAT 3525, 3526, 3505
- Eaton Vickers
- Ford M2C86B, C
- JCMAS HK P-041, P-042
- John Deere J20C, J20D

TYPICAL CHARACTERISTICS

• Kubota UDT, Super UDT

- Massey Ferguson: M1145
- Parker (Denison) HF-0, HF-1, HF-2
- VCE 1273.03
- Volvo WB101
- White Q-1826
- ZF TE-ML-03E
- ZF TE-ML-03F

- ZF TE-ML-05F
- ZF TE-ML-06E
- ZF TE-ML-06F
- ZF TE-ML-06K
- ZF TE-ML-17E ZF TE-ML-21F

AGRI MONO T2 30W	UNITS	VALUES
VISCOSITY	cSt @ 40°C	102.6
	cSt @ 100°C	11.4
SPECIFIC GRAVITY	@ 15°C	0.877
VISCOSITY INDEX		97
POUR POINT	°C	-15
FLASH POINT	°C	234

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice. [®] Vertex is a registered trademark of Lubricants NZ Ltd.





ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.