

TRANSMATIC CVT MV PLUS

PRODUCT DESCRIPTION

Transmatic CVT MV Plus is a Synthetic Transmission Fluid blended with high-performance synthetic base oils and high-performance additives, including friction modifiers, detergent-dispersants, oxidation inhibitors, viscosity index improvers, corrosion inhibitors, and defoaming agents. Transmatic CVT MV Plus is a multi-vehicle automatic transmission fluid which provides suitable performance in a wide range of CVT-equipped passenger vehicles which transfer traction via steel-made traction chains or belts. It provides outstanding power transmission ratios and better fuel-economy performance in modern CVT transmissions.

APPLICATIONS & BENEFITS

- High performance additives and synthetic base stocks capable of servicing a wide range of CVT transmissions.
- Provides excellent friction, oxidation, and thermal stability.
- Outstanding anti-wear properties and oil film thickness.
- Excellent shear stability for consistent shift.
- Compatible with a wide range of seals.

PACK SIZES AVAILABLE

1L - 5L - 20L - 200L

SPECIFICATIONS

- AUDI / VW P/N G 052 180 (-A2)
- AUDI / VW P/N G 052 516 A2
- DAIHATSU AMMIX CVTF-DFE
- DAIHATSU AMMIX CVTF-DTC
- DODGE / JEEP NS-2
- FCA CVTF+4 P/N 05191184AA
- GM CVTF I-GREEN2
- GM CVT P/N 19260800
- HONDA HCF-2 P/N 08200-HCF2
- MAZDA CVTF 3320
- MITSUBISHI DIAMOND GREEN CVTF-J1
- MITSUBISHI DIAMOND GREEN CVTF-J4
- NISSAN NS-1
- NISSAN NS-2
- NISSAN NS-3
- RENAULT ELF MATIC
- SHELL GREEN 1V
- SUBARU LINEARTRONIC CVTF
- SUBARU LINEARTRONIC CVTF-II; P/N K0425Y0711
- SUBARU LINEARTRONIC CV-30 P/N K0425Y0710
- SUBARU e-CVTF
- SUBARU HIGH TORQUE P/N K0421Y0700
- SUZUKI CVT FLUID GREEN 1
- SUZUKI CVT FLUID GREEN 2
- SUZUKI CVTF 3320
- SUZUKI NS-2
- TOYOTA / LEXUS FE
- TOYOTA / LEXUS TC

TYPICAL CHARACTERISTICS

TRANSMATIC CVT MV PLUS	UNITS	VALUES
VISCOSITY	cSt @ 40°C	34.4
	cSt @ 100°C	7.2
SPECIFIC GRAVITY	@ 15°C	0.8537
VISCOSITY INDEX		180
POUR POINT	°C	-45
FLASH POINT	°C	198
BROOKFIELD VISCOSITY	@ -40°C	13500

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.