

TRANSMATIC DX-6

PRODUCT DESCRIPTION

Vertex Transmatic DX-6 is a Fully Synthetic Low Viscosity Multi ATF formulated to service Automatic Transmissions in Passenger Motor Vehicles. Fully Synthetic Base Stocks and Advanced Additives provide unsurpassed protection and compatibility in a wide range of Passenger Vehicle Transmissions requiring a low viscosity fluid. Transmatic DX-6 is compatible for transmissions requiring Toyota Type WS, Nissan Matic S, Hyundai SP-IV, Ford Mercon LV and GM Dexron HP and VI.

APPLICATIONS & BENEFITS

- Fully Synthetic Multi ATF designed to provide the ultimate protection in transmissions requiring a low viscosity fluid.
- Provides excellent oxidation and thermal stability for longer service life.
- Superior wear protection of all critical transmission components.
- Excellent rust and corrosion protection.

PACK SIZES AVAILABLE

1L - 5L - 20L - 60L - 200L - 1000L IBC

SPECIFICATIONS

- | | | |
|--|---|---|
| • AISIN JWS 3324 ATF, ATF-OWS | • GM AW1, P/N 19256039, Dexron HP [GMW 16974] | • Mitsubishi Dia Queen ATF-PA, P/N 4030401 |
| • ATF 134 | • GM WS, P/N 88863400 | • Mitsubishi SP-IV |
| • ATF 3353 | • GM WS, P/N 88863401 | • Nissan Matic R, P/N 999MP-MTR00P |
| • ATF L12108 | • Honda / Acura ATF DW-1 P/N (08200-9008) | • Nissan Matic S, P/N 999MP-MTS00P |
| • ATF M-1375.4 | • Honda / Acura ATF Type 3.0 (08200-9016-A) | • Nissan Matic W |
| • ATF M-1375.6 | • Honda / Acura ATF Type 3.1 (08200-9017) | • Porsche P/N 000 043 304 00 |
| • Bentley P/N PY112995PA | • Hyundai / Kia ATF SP-IV | • Porsche P/N 000 043 304 01 |
| • BMW ATF 3+ | • Hyundai / Kia P/N 040000C90SG | • Porsche P/N 000 043 305 43 |
| • BMW ATF 6 | • Hyundai / Kia SP4-M1 | • Porsche P/N 000 043 305 54 |
| • BMW M-L12108 | • Hyundai / Kia SP-IV | • Porsche P/N 000 043 306 24 |
| • BMW P/N 83 22 0 142 516 | • Hyundai / Kia SP-IV-RR, WS, spec NWS-9638 | • Porsche P/N 958 300 540 00 |
| • BMW P/N 83 22 0 397 114 | • Isuzu ATF WSI | • Saab P/N 93 165 147 |
| • BMW P/N 83 22 2 152 426 | • Isuzu SCS | • Subaru ATF-WS |
| • BMW P/N 83 22 2 163 514 | • Jaguar 02JDE 26444 | • Suzuki Matic S |
| • BMW P/N 83 22 2 289 720 | • Jaguar Fluid 8432 | • Toyota ATF FZ |
| • BMW P/N 83 22 2 305 396 | • JAMA JASO M315, Class 1-A-LV(1) | • Toyota JWS 3324, ATF WS (or NWS9638) |
| • BMW P/N 83 22 2 305 397 | • Land Rover AW-1 P/N LR0022460: LV | • Volvo P/N 31 256 774, 31 256 775 |
| • BMW P/N 83 22 2 355 599 | • Land Rover LR 023288/023289 | • Volkswagen / Audi G 052 533 |
| • BMW P/N 83 22 2 355 601 | • Land Rover P/N TYK500050 | • Volkswagen / Audi G 055 005 A2 |
| • FCA 8 & 9 Speed ATF, P/N 68218925AA/AB | • Maserati Oil No. 231603 | • Volkswagen / Audi G 055 162 A2 or A6 |
| • FCA AW-1, P/N 68092912AA | • Mazda ATF FZ | • Volkswagen / Audi G 055 540 A2 |
| • FCA Fiat 9.55550-AV2 | • Mercedes MB 236.12 | • Volkswagen / Audi G 060 162 A2 |
| • FCA Fiat 9.55550-AV5 | • Mercedes MB 236.14 | • ZF LifeguardFluid 6 (ZF No. S671 090 255) |
| • FCA Fiat 9.55550-AV6 | • Mercedes MB 236.41 | • ZF LifeguardFluid 8 (ZF No. S671 090 312) |
| • FCA P/N 05127382 | • Mitsubishi ATF-J3 | • ZF LifeguardFluid 9 (ZF No. AA01.500.001) |
| • FCA P/N 68157995AA/AB | • Mitsubishi Dia Queen ATF-MA1, P/N MZ320775 | |
| • FCA SP-IV, P/N 68171866AA | | |
| • FCA SP-IV, P/N 68171869AA | | |
| • Ford Mercon SP | | |
| • Ford Mercon LV | | |
| • GM Dexron VI | | |

TYPICAL CHARACTERISTICS

TRANSMATIC 295	Method	Results
Specific Gravity @ 15 °C	ASTM D 4052	0.845
Flash Point, °C	ASTM D 92	198
Pour Point, °C	ASTM D 97	-45
Kinematic Viscosity, cSt @ 40°C	ASTM D 445	26.72
cSt @ 100°C	ASTM D 445	5.66
Viscosity Index	ASTM D 2270	160

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 26 July 2024.

The information contained in this Product Data Sheet is accurate at the time of printing and is subject to change without prior notice.

* Vertex is a registered trademark of Vertex Lubricants NZ Ltd.