

TRANSGEAR DCT LL

PRODUCT DESCRIPTION

Transgear DCT LL is a premium synthetic Automatic Dual Clutch Transmission fluid suitable for use in Hybrid DCT's in addition to conventional wet DCT's. The product contains specially selected high viscosity index synthetic base stocks and the latest additives providing an impressive range of OEM transmission compatibility, making the product suitable for use in a wide range of vehicles. Extensive research in the use of top tier components has resulted in a product ensuring excellent transmission durability, oxidation stability and friction durability for extended shudder free operation, pump efficiency and material and copper compatibility. Transgear DCT LL is the optimum choice for most modern and conventional Hybrid vehicles. Transgear DCT LL is suitable for use in VW, Seat and Skoda 6-speed wet Dual Clutch Transmissions (2003 to present), Ford, Volvo, Mitsubishi, PSA and Chrysler 6-speed wet Dual Clutch Transmissions (2007 to present) and 7-speed wet Dual Clutch Transmissions from VW, Magna, Geely and Great Wall.

APPLICATIONS & BENEFITS

- Advanced additive package delivers a wide range of OEM transmission compatibility.
- Provides excellent oxidation and thermal stability for long-life operation.
- Superior wear, rust and corrosion protection maintains critical transmission components.
- Fully Synthetic formulation provides stable viscosity during heavy load operation.

PACK SIZES AVAILABLE

1L - 5L - 20L - 200L

SPECIFICATIONS

- Audi VW TL G 052 182
- Audi VW TL G 052 529
- BMW (Getrag) 83 22 0 440 214
- BMW (Getrag) 83 22 2 147 477
- BMW (Getrag) 83 22 2 148 578
- BMW (Getrag) 83 22 2 148 579
- Citroen Peugeot / Citroen 9734.S2
- Ford / Getrag Ford M2C936A
- Mercedes-Benz MB 236.21
- Mercedes-Benz MB 236.25
- Mitsubishi MZ320065 Dia-Queen
- Mitsubishi Dia Queen SSTF-1
- Nissan Ford M2C936A
- Peugeot Peugeot / Citroen 9734.S2
- Porsche (ZF) 999.917.080.00
- Seat VW TL G 052 182
- Skoda VW TL G 052 182
- Volkswagen VW TL G 052 182
- Volvo 1161838 / 1161839

TYPICAL CHARACTERISTICS

TRANSGEAR DCT LL	UNITS	VALUES
VISCOSITY	cSt @ 40°C	32.9
	cSt @ 100°C	7.17
SPECIFIC GRAVITY	@ 15°C	0.8449
VISCOSITY INDEX		190
POUR POINT	°C	-45
FLASH POINT	°C	198
Viscosity, Brookfield	@ -40°C, mPa.s	8572

ADDITIONAL INFORMATION

Designed for New Zealand Conditions | Manufactured from virgin base stocks. For more technical information please contact Vertex Lubricants NZ Technical Dept. +64 9 640 0004. Sheet updated 27 June 2023.